


板面除塵清潔機 PANEL CLEAN MACHINE SERIES

YC-650-2S

■ 特徵 Features:


- 1038L x 330W x 1275H
- 滾輪專利機構，可拉出除塵滾輪耦合傳動
Patented cleaning roller mechanisms; extractable cleaning roller with coupling transmission
- 適合板厚0.1~3.2mm
Workable board thickness:0.1~3.2mm

專利產品
(PATENTED)

YC-650-4S

■ 特徵 Features:


- 1040L x 380W x 1280H
- 滾輪專利機構，可拉出除塵滾輪耦合傳動
Patented cleaning roller mechanisms; extractable cleaning roller with coupling transmission
- 多組滾輪、黏紙捲清潔
Several sets for cleaning roller and adhesive roll for cleaning
- 適合板厚0.1~3.2mm
Workable board thickness:0.1~3.2mm

專利產品
(PATENTED)

YC-650-6S

■ 特徵 Features:


- 1046L x 516W x 1263H
- 滾輪專利機構，可拉出除塵滾輪耦合傳動
Patented cleaning roller mechanisms; extractable cleaning roller with coupling transmission
- 多組滾輪、黏紙捲清潔
Several sets for cleaning roller and adhesive roll for cleaning
- 適合板厚0.1~3.2mm
Workable board thickness:0.1~3.2mm

專利產品
(PATENTED)

YC-650-10S

■ 特徵 Features:

- 1130L x 975W x 1263H
- 滾輪專利機構，可拉出除塵滾輪耦合傳動
Patented cleaning roller mechanisms; extractable cleaning roller with coupling transmission
- 多組滾輪、PLC控制，人機操作
Several sets for cleaning roller, PLC Control, user-friendly human machine interface touch panel
- 適合板厚0.1~3.2mm
Workable board thickness:0.1~3.2mm

專利產品
(PATENTED)

板面除塵清潔機 PANEL CLEAN MACHINE SERIES

YC-650TF12R-6S

■ 特徵 Features:

1. 特別適用軟板、薄板。
Especially suitable for thin film, and panel.
2. 除塵滾輪及黏紙捲各具調壓機能; PLC控制
PLC control, pressure adjustment is applicable with each of cleaning rollers and adhesive rolls.
3. 另有手動模式使除塵滾輪持續接觸運轉, 以應付特殊狀況。
Manual mode is applicable to keep cleaning rollers in contact in special cases.
4. 待機時, 黏紙捲自動分離。
Adhesive rolls to separate automatically while non running.
5. 人機介面觸控面板, 便於操作及設定, 可設定管理密碼, 避免操作人員擅自更改設定, 具有卡板警示功能, 迅速提供操作人員問題排除。
A user-friendly human machine interface touch panel for easy operation and setting. Able to set the administrator's password to prevent from others to change the setting. The alarm function of PCB jam, to provide operator solve the problem immediately.
6. 專利機構: Patented mechanisms:
 - A. 抽出滾輪之耦合及傳動機構—順暢、耐用, 抽出時不需開機。
Smooth coupling and transmission for cleaning roller drawer.
 - B. 除塵滾輪之驅動氣壓管路—結構簡化, 節省空間。
Activating piping circuits for cleaning rollers.
 - C. 軟板專用機構特徵:
Features on mechanism for thin film:
(1) 特殊滾輪傳動架構及間距—防止軟薄板之捲曲及掉落。
Specially aligned roller diameter and pitch, to avoid curling or falling of work.
(2) 獨創抗靜電滾輪—除塵效果更佳。
Anti-static rollers to further improve cleaning.
(3) 特殊退出導輪設計—確保軟板輸送順暢, 維持平整。
Specially designed guide rollers at entrance and exit, ensuring smooth transmission and flat work.

專利產品
(PATENTED)軟、薄板專用機
New for Thin Film or FPC

■ 規格 YC-650TF12R-6S

規格 YC-650TF12R-6S	電源: 220V/380V / (50/60HZ)
工作物寬: 50~650 mm	空氣壓: 6kg/cm ²
工作物厚: 0.05~1.6mm	本體尺寸: 1046L x 742W x 1237H
除靜電棒: 進出口上方各一支	淨重: 約450kg

YC-650TC4R-2S

■ 特徵 Features:

- 1038L x 330W x 1275H
切溝式滾輪設計, 除塵滾輪及黏紙捲各具調壓機能
Design for cutting cleaning roller, pressure adjustment is applicable with each of cleaning rollers and adhesive rolls
適合軟、薄板清潔
Suitable for thin film and panel
適合板厚 0.05~1.6mm
Workable board thickness: 0.05~1.6mm


專利產品
(PATENTED)

板面除塵清潔機 PANEL CLEAN MACHINE SERIES

YC-650V

■ 特徵 Features:


- 920L x 235W x 1180H
- 標準的泛用機種，除塵滾輪採固定(不拉出)機構
Standard model for general application; non-extractable cleaning roller
- 適合板厚 0.1~3.2mm
Workable board thickness: 0.1~3.2mm



YC-1500 (鋼板系列)

■ 特徵 Features:


- 2106L x 420W x 1600H
- 壓合鋼板專用
Suitable for CCL Caul Plate
- 堅固耐用
Durable
- 適合板厚 0.5~4mm
Workable board thickness: 0.5~4mm
- 適用型號 YC-1360、YC-1420
suitable for model YC-1360、YC-1420



YC-650TF4R-2S

■ 特徵 Features:


- 1038L x 330W x 1275H
- 滾輪間距小，除塵滾輪及黏紙捲各具調壓機能
Small space among cleaning rollers, pressure adjustment is applicable with each of cleaning rollers and adhesive rolls
- 適合軟、薄板清潔
Suitable for thin film and panel
- 適合板厚 0.05~1.6mm
Workable board thickness: 0.05~1.6mm

專利產品
(PATENTED)

YC-650TF8R-4S

■ 特徵 Features:

- 1046L x 379W x 1249H
- 滾輪間距小，除塵滾輪及黏紙捲各具調壓機能
Small space among cleaning rollers, pressure adjustment is applicable with each of cleaning rollers and adhesive rolls
- 適合軟、薄板清潔
Suitable for thin film and panel
- 適合板厚 0.05~1.6mm
Workable board thickness: 0.05~1.6mm

專利產品
(PATENTED)

板面除塵清潔機 PANEL CLEAN MACHINE SERIES

YC-650VP

■ 特徵 Features:

1138L x 610W x 1428H

垂直式清潔，方便一人獨立作業


Vertical direction for cleaning, easy for one person to operate independent

不佔用空間，可隨時移動作業場所

A place is not taken, able to move the working place when necessary

適合板厚 1.6~3.2mm

Workable board thickness: 1.6~3.2mm



YC-300TF4R-2S

(MINI TYPE ESPECIAL FOR THIN FILM)

■ 特徵 Features:

可選擇往復、不往復; PLC控制。

Auto reverse or none by customer, PLC control.

除塵滾輪可整組抽出，便於保養。

Retractable of clean roll for easy maintain

桌上型，適合軟板小尺寸及液晶面板不佔空間。

Working table, a place is not taken.

The best for small works, such as FPC

可拆式輸送架。

Re-movable conveyor for easy taking out. .

